

Model Name	Nominal power (H.P.)	Nominal Capacity (H.P.)	Displ.(cm <sup>3</sup> )	Oil charge(cm <sup>3</sup> )	Weight(kg)	Power supply	Refrigeration Capa	
							-45°C	-40°C
							Q1.5L	1
Q2.0L	1.5	1600	58.4	1200	28	805	626	
Q2.2L	2	2200	61.9	1600	38	992	640	
Q2.2AL	3	3140	79.6	1600	39	1561	1203	
Q2.2SL	2	2200	61.9	1600	37	992	640	
Q2.2SAL	3	3140	79.6	1600	38	380V/50H Z/3PH	1561	1203
Q3.2SL	3.5	3560	90.4	1600	37		1772	1361
Q4.5SAL	4	4360	113	1600	48		1696	1107
Q5.0SAL	5	4940	125	1980	48		2118	1710
Q5.0SL	6	5530	139	1980	49		2451	2012

Capacity at 50Hz rated @54.5°C/130°F Cond.Temp (Watts)					Run Capacitor (µF/450V)
Evaporating Temperature					
-35°C	-30°C	-23.3°C	-20°C	-10°C	
549	797	1190	1423	229	35
723	1076	1600	1902	3012	40
738	1319	2200	2662	4419	40
1380	2016	3140	3796	6222	50
738	1319	2200	2662	4419	
1380	2016	3140	3796	6222	
1560	2290	3560	4390	7060	
1743	2704	4360	5335	9038	
2215	3131	4940	6011	10050	
2378	3545	5530	6688	11062	