

Technical data and ordering



Pressure controls for fluorinated refrigerants

| Pressure | Type | Low pressure (LP) | | High pressure (HP) | | Reset | | Contact system | Code no. | | | |
|----------|-------|------------------------|-------------------------------|------------------------|-------------------------------|---------------------|---------------------|--------------------------|-----------------------------|--------------------------|--------------------------|---|
| | | Regulating range [bar] | Differential Δp [bar] | Regulating range [bar] | Differential Δp [bar] | Low pressure LP | High pressure HP | | 1/4 in. 6 mm flare | 1/4 in. ODF solder | 6 mm ODF solder | |
| Low | KP 1 | -0.2 - 7.5 | 0.7 - 4 | - | - | Aut. | - | SPDT | D60-110166 ^{f)} | 060-111266 ^{g)} | 060-111066 ^{g)} | |
| Low | KP 1 | -0.2 - 7.5 | 0.7 - 4 | - | - | Aut. | - | | D60-114166 ^{f)} g) | - | - | |
| Low | KP 1 | -0.9 - 7 | 0.7 | - | - | Man. | - | | D60-110366 | 060-111166 | 060-110966 | |
| Low | KP 2 | -0.2 - 5 | 0.4 - 1.5 | - | - | Aut. | - | | D60-112066 ^{f)} | - | 060-112366 ^{g)} | |
| High | KP 5 | - | - | 8 - 32 | 1.8 - 6.0 | - | Aut. | | D60-117166 ^{f)} | 060-117966 ^{g)} | 060-117766 ^{g)} | |
| High | KP 5 | - | - | 8 - 32 | 3 | - | Man. | | D60-117366 | 060-118066 | 060-117866 | |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Aut. | Aut. | | SPDT + LP signal | D60-124166 ^{f)} | 060-125466 ^{g)} | - |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Aut. | Man. | | | D60-124366 | - | - |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Aut. | Man. | | | D60-114866 ^{f)} | - | - |
| Dual | KP 15 | -0.9 - 7 | 0.7 | 8 - 32 | 4 | Man. | Man. | | | D60-124566 | - | - |
| Dual | KP 15 | -0.9 - 7 | 0.7 | 8 - 32 | 4 | Conv. ²⁾ | Conv. ²⁾ | D60-126166 | | - | - | |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Aut. | Aut. | D60-126566 ^{f)} | | 060-129966 ^{g)} | - | |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Aut. | Man. | SPDT + LP and HP signal | D60-126466 | 060-128466 | - | |
| Dual | KP 15 | -0.2 - 7.5 | 0.7 - 4 | 8 - 32 | 4 | Conv. ²⁾ | Conv. ²⁾ | | D60-115466 ^{f)} | 060-001066 ^{g)} | - | |
| Dual | KP 15 | -0.9 - 7 | 0.7 | 8 - 32 | 4 | Conv. ²⁾ | Conv. ²⁾ | | D60-122066 | - | - | |